



COMBINATION SHOWER/ FACEWASH WITH S/S BOWL & PLASTIC BOWL COVER

PART NUMBER: 01050234PBC

SPECIFICATION:

The Encon combination shower and eye/facewash shall deliver 30 gpm (113.6 lpm) water from the shower head and 8.0 gpm (30.3 lpm) to assure a constant, even dual stream flow pattern under 30/70 psi (144 lpm @ 206.8/482.6 kPa) from the eye/facewash in non-injurious patterns. Shower head must deliver a minimum of 20" (50.8 cm) diameter pattern to the target area 60" (152.4 cm) above standing level. Combination units that provide improper flow pattern or contain deteriorating screens/filters are not acceptable. The bowl is a type 304 SS and includes a highly visible ABS cover to inhibit dust and/or particulate accumulation on the eyewash heads when not in use. The cover shall open immediately on actuation of the eye/face wash valve and will be able to be opened or closed manually, separate of the eye/face wash actuator, to allow for ease of maintenance of the eye/face wash nozzle assembly under the bowl cover. The shower and eye/face wash shall be third party certified to meet the ANSI Z358.1 standard.

Encon Safety Products Model 01050234PBC includes combination shower/facewash with stainless steel bowl and plastic bowl cover

***Note:** Where hazardous materials that are injurious to the skin are used, a proper eyewash or eye/facewash installation with an emergency shower should be considered.

MATERIALS OF CONSTRUCTION:

PIPING: Schedule 80 hot dip galvanized steel.

VALVES: Chrome plated bronze stay open ball valves with chrome plated balls, stainless steel valve stems, stainless steel push plate with actuation graphic (eye/facewash) and stainless steel pull rod assembly with actuation graphic (shower). Valve sizes: shower 1", eye/facewash 1/2". Strainer Tee Option: 1/2" BCP, 16 mesh

SHOWER HEAD: Yellow ABS plastic shower head.

EYE/FACEWASH HEAD: UV resistant ABS plastic dual stream heads mounted on a low profile chrome plated brass wye with ABS plastic float off covers secured with stainless steel bead chains. Includes a brass retainer for the regulators.

BOWL: Type 304 stainless steel bowl and an ABS cover attached with vinyl coated actuating cable and stainless steel hardware.

REGULATOR: Shower head shall have a self-adjusting 30 gpm (113.6 lpm) regulator. Eye/Facewash shall have a self-adjusting 8.0 gpm (30.3 lpm) regulator to assure a constant and even dual stream flow pattern under 30/70 psi (206.8/482.6 kPa) hydraulic conditions.

SUPPLY: 1 1/4" NPT

WASTE: 1 1/4" NPT

WEIGHT: 60 lbs (27.21 kgs)

