



COUNTER MOUNT EYEWASH/ DRENCH HOSE DUAL STREAM PART NUMBER: 01090012

SPECIFICATION:

Third party certified to ANSI Z358.1, the drench hose shall deliver 2.4 gpm (9.1 lpm) @ 30/70 psi (206.8/482.6 kPa) of flowing pressure. Unit shall provide a non-injurious stream of water for 15 minutes or longer. Unit shall be supplied with 3/8" chrome plated (CP) bronze self closing lockable squeeze valve. Unit shall include actuator, 7" x 11" (17.8 cm x 27.9 cm) sign, 8-foot (182.9cm) synthetic rubber hose, sink/countertop mounting bracket and 3/8" NPT connection. Unit must be supplied with self-adjusting 2.4 gpm (9.1 lpm) regulator on the drench hose/eyewash to assure a constant and even dual stream flow pattern under 30/70 psi (206.8/482.6 kPa) hydraulic conditions. Drench hose/eyewash heads with hinged covers to be manufactured of solvent resistant acetal plastic mounted on a chrome plated brass wye. Covers are provided to inhibit dust and/or contamination when not in use. Drench hose units with deteriorating screens/filters are not acceptable.

Encon Safety Products Model 01090012 includes counter mount eyewash/drench hose unit.

*This unit will qualify as an eyewash station when properly mounted to meet Section 5 of ANSI Z358.1-2014.

*Mount 33" to 45" high with 6" from any obstruction and position for hand-free operation to use as an eyewash per ANSI Z358.1-2014.

***Note:** Where hazardous materials that are injurious to the skin are used, a proper eyewash or eye/facewash installation with an emergency shower should be considered.

MATERIALS OF CONSTRUCTION:

VALVE: 3/8" Chrome plated bronze self-closing squeeze valve with lock open handle actuator.

PIPING: Chrome plated brass.

HEAD: Acetal dual stream heads with integral hinged covers and chrome plated brass wye assembly.

REGULATOR: Self-adjusting (2) 1.2 gpm (4.5 lpm) regulators.

HOSE: 8' (243.8cm) synthetic rubber hose.

SUPPLY: 3/8" NPT (1/2" supply line recommended).

WEIGHT: 7 lbs (3.17 kgs)

